

Viewtech Wireless Camera Solution



7" & 9" Monitor Options / Heavy Duty / 3 Year NZ/AU Warranty

The Viewtech Wireless range is a suite of equipment suitable for material handling as well as other applications where a wireless camera and monitor solution is needed.

24/7 Duty Cycle allows this system to be left on all the time for demanding applications.

Applications

- Forklifts
- Telehandlers
- Container Handlers
- Cranes
- Trucks & Trailers

Main Features

- Wireless video transmission
- 7" and 9" Monitor Options (both quad camera viewable)
- camera trigger inputs
- Up to 100m wireless range

Camera Options

Camera and Lens options allow different mounting options and viewing angles.

VT671DW - Conventional bracket 120° FOV

VT671DW-69 - Conventional bracket 69° FOV

VT268FL - Slim Line Magnetic base & screw mount - 44° FOV

VT697DWB - Magnetic Mount with built in battery 120° FOV

Built in Recording Feature

Built in SD card recording saves video direct to a micro SD card. This can then be retrieved and played back on any PC.

For more advanced recording options and remote access use Viewtech Fleetview.

Ordering Info & Common Kits

VT7WQDVR 7" Kit with VT671DW camera

VT9WQDVR 9" Kit with VT671DW camera

VT7W268FL 7" Kit with VT268FL camera

VT9W268FL 9" Kit with VT268FL camera



VT671DW Camera



VT697DWB Camera

This unique camera has a built in battery and super strong magnetic base. It can work up to 8 hours on a single charge and has built in battery management. Charge from 12V-30V or USB.



VT268FL Camera



3-5 YEAR
NZ/AU WARRANTY



24-HOUR
SUPPORT



ONLINE
ASSISTANCE



SMART
TECHNOLOGY



FIT FOR
PURPOSE

0800 888 324
viewtech.co.nz

Optional Parts & Specifications

VT509 Battery

The battery option is used if there is no hardwired power at the location the camera is to be mounted. This battery has built in battery management and can be charged by 12V-30V DC.

The battery will run for around 6 hours of use. VT12V1A is a battery charger available for this pack.




VT509 Camera Battery



VT550 Clamp Mount



VT540 Overhead Mount



VTAC539 Magnetic Camera Mount



VT42ANT3M

VT42ANT3M

VT42ANT3M is a small directional panel antenna which can be used on the VT671DW cameras for increasing connectivity at either the camera or the screen end. Only use in the rare occurrence of range or connection issues.

Specifications				
Monitor	VT7DWQ 7"	VT9DWQ 9"		
Viewable Panel Size	7"	9"		
Wireless Video Inputs	4			
Video Viewing Modes	Single, Split Screen, Quad Screen			
Recording	Yes, up to 256GB Micro SD Card			
Camera Triggering	Single or Split Screen			
Vibration	ISO 16750-3 5.9G			
Auto Dimming	Yes			
Temperature	-30°C - 60°C			
Power	10V-32V			
Dimensions (mm)	213w x 137h x 26d	230x x 150h x 45d		
Camera	VT671DW	VT671DW-69	VT268FL	VT697DWB
Sensor	600TVL			
Viewing Angle	120°	69°	44°	120°
Min Illumination	0.0Lux with IR on			
Built In Battery	No	No	No	Yes 6hr-8hr
Infrared	Smart IR with 5m Range			
Heater	Yes <10°C			
Audio	Yes			
Size	86w x 72h x 75d	86w x 72h x 75d	35w x 35h x 120d	120w x 80h x 150d
Power	10V-32V			
Vibration	ISO 16750-3 5.9G			
Temperature	-30°C - 60°C			
RF Bit Rate	12Mbps			



3-5 YEAR
NZ/AU WARRANTY



24-HOUR
SUPPORT



ONLINE
ASSISTANCE



SMART
TECHNOLOGY



FIT FOR
PURPOSE

0800 888 324
viewtech.co.nz